


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : A43B 5/16, A43C 1/00, A43B 5/00</p>	<p>A1</p>	<p>(11) International Publication Number: <b>WO 98/37782</b> (43) International Publication Date: 3 September 1998 (03.09.98)</p>
<p>(21) International Application Number: PCT/CA98/00154 (22) International Filing Date: 24 February 1998 (24.02.98) (30) Priority Data: 2,198,448 25 February 1997 (25.02.97) CA (71) Applicant (for all designated States except US): BAUER INC. [CA/CA]; Suite 600, 8000 Decarie Boulevard, Montreal, Quebec H4P 2S4 (CA). (72) Inventor; and (75) Inventor/Applicant (for US only): RACINE, Bertrand [CA/CA]; 303 Lacharité Avenue, LaSalle, Quebec H8P 2B9 (CA). (74) Agents: GEORGIEV, Stephan, P. et al.; Smart &amp; Biggar, Suite 3400, 1000 de la Gauchetière Street West, Montreal, Quebec H3B 4W5 (CA).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>
<p>(54) Title: ROLLER SKATE BOOT LACING SYSTEM</p> <p>(57) Abstract</p> <p>A skate boot comprising an outer shell and an inner liner, said shell and liner being provided with an opening generally adapted to substantially correspond at least partially with a portion of the dorsal area of the foot of the wearer, said liner and said shell being provided with attachment means for engagement with a lace, said attachment means being disposed such that at least a pair of said attachment means of said shell is disposed adjacent a pair of said attachment means of said liner to form an alternate lacing arrangement.</p> 		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## Roller Skate Boot Lacing System

### Field of the Invention

The present invention relates to roller skates, and more particularly to a lacing  
5 system for roller skates boots comprising a rigid outer shell and an inner boot  
liner.

### Background of the Invention

Since their original conception over 100 years ago, the design of roller skates  
10 has undergone several changes. Today, although the activity remains a popular  
one, the type of skate most preferred by skaters is the in-line skate, as opposed  
to the four-wheel bi-axle skates of old. Several different constructions of skates  
are known in the art and many are currently available on the market. One of the  
15 more popular constructions is the ski boot style in-line skate. In this type of  
skate, the skate boot generally comprises a rigid plastic boot or shell to which  
is attached the wheel frame which provides a mounting for the wheels. The  
upper portion of the rigid shell is open over the dorsal part of the foot of a skater  
and a tongue, for example attached to the rest of the boot in the area of the  
20 skater's toes, may be disposed within the open portion. This construction allows  
the skater to more easily put on and take off the skate. Conventional fastening  
systems, such as laces or buckles, are used to tighten and secure the skate  
boot around the foot of the skater.

In order to provide for his comfort and to prevent injury to the skater, a liner,  
25 typically comprising a soft cotton or other textile is provided within the rigid  
plastic material of which the outer part of the boot is constructed. The skater  
actually inserts his foot into the liner, and it is the liner which is in direct contact  
therewith during the use of the skate.

It has been previously realised, that in order to provide the skater with the best control and performance possible, the efficiency of the transfer of force from his body to the skating surface, and *vice versa*, should be maximised; stray forces should be avoided. Skate boots of the aforementioned construction, however,  
5 do not provide for maximal efficiency of force transfer and thus for the best performance and control as the liner is capable of moving within the boot in response to the forces generated during skating.

A skate boot construction wherein the liner is secured so as to limit its  
10 movement within the shell during skating is thus desired so as to provide the skater with improved control and performance.

#### **Object and Statement of the Invention**

It is thus an object of one aspect of the present invention to provide a roller  
15 skate wherein the liner is arranged so as to limit its movement within the rigid outer shell of the skate boot during skating.

As embodied and broadly described herein, the present invention provides a lacing system for a boot, said boot comprising a first outer member and a  
20 second inner member, said lacing system comprising a first set of attachment means provided on said first outer member, and a second set of attachment means provided on said second inner member, wherein at least a pair of attachment means of each set is disposed such that a single lacing means provided on said boot is capable to engage alternately the first outer member  
25 and the second inner member.

The shell and the liner of a boot using such a system are capable of being co-laced, *i.e.* it is possible to lace-up and tighten the shell and the liner by a single lace. The foot is thus well maintained and the force transfer from the foot to the  
30 frame of the skate is increased.

Preferably, the attachment means comprises eyelets and/or straps and/or hooks or the like. The boot provided with such a system can thus be configured according to an almost unlimited number of possibilities.

5

As embodied and broadly described herein, the present invention also provides a skate boot comprising an outer shell and an inner liner, said shell and liner being provided with an opening generally adapted to substantially correspond at least partially with a portion of the dorsal area of the foot of the wearer, said  
10 liner and said shell being provided with attachment means for engagement with a lace, said attachment means being disposed such that at least a pair of said attachment means of said shell is disposed adjacent a pair of said attachment means of said liner to form an alternate lacing arrangement.

15 The shell and the liner are capable of being co-laced, *i.e.* it is possible to lace-up and tighten the shell and the liner by a single lace. The foot is thus well maintained and the force transfer from the foot to the frame of the skate is increased.

20 Preferably, the lacing arrangement is such that a lacing means provided on said boot is capable to alternately engage said liner attachment means and said shell attachment means. The alternate arrangement provides an efficient force distribution between the liner and the shell. The sequences or alternations between the liner and the shell may vary from one example to the other. In other  
25 words, the lace could pass  $x$  times through the liner and  $y$  times through the shell,  $x$  and  $y$  being equal or different numbers.

Preferably, the attachment means comprises eyelets and/or straps and/or hooks or the like. This provides a vast choice of designs for the boot.

30

Other objects and features of the invention will become apparent by reference to the following description and the drawings.

**Brief Description of the Drawings**

- 5 A detailed description of preferred embodiments of the present invention is provided hereinbelow with reference to the following drawings, in which:

Figure 1 is a perspective view of the skate boot of the present invention;

- 10 Figure 2 is a perspective view of a second embodiment of the skate boot of the present invention;

Figure 3 is an exploded perspective view of the liner and the shell of a skate boot according to the invention;

15

Figures 4 to 6 are top views of variants of the skate boot of the invention with illustrating different lacing sequences or alternations.

- 20 In the drawings, preferred embodiments of the invention are illustrated by way of example. It is to be expressly understood that the description and drawings are only for purposes of illustration and as an aid to understanding, and are not intended to be a definition of the limits of the invention.

**Detailed Description of Preferred Embodiments**

- 25 Referring to Figure 1, a skate boot 10 of the present invention comprises a substantially rigid outer shell 12, sometimes referred to as plastic lower of skate and a liner 14. Both the shell 12 and the liner 14 are constructed of conventional materials and in accordance with methods familiar to those skilled in the art. As a non-limiting example, the shell 12 may be constructed of an

injection-moulded plastic, and the liner 14 of a machine-woven cotton or cotton/polyester blend.

Both the shell 12 and the liner 14 have a longitudinal opening 16 along the dorsal area of the foot. Along each side of the opening 16 in the shell 12, there is provided a plurality of shell attachment means 18, for example eyelets, adapted to receive a lacing means 20, for instance a lace or the like, so as to allow the shell 12 to be tightened about the foot of the skater. Similarly, attached to the liner 14 on each side of the opening 16, there is provided a plurality of liner attachment means 22, for instance straps, adapted to receive a lacing means 20, for instance a lace or the like, so as to allow the liner 14 to be tightened about the foot of the skater.

In this embodiment, the eyelets 18 and the straps 22 are alternately exposed such that the single lace 20 is capable of co-lacing both the shell 12 (through the eyelets 18) and the liner 14 (through the straps 22). In this configuration, illustrated in figure 1, starting from the toe and working up the skate boot, the skate boot is constructed so that the lace is alternately laced through an eyelet 18 of the shell 12 and a strap 22 of the liner 14. Such a configuration is not however required. In accordance with the present invention, it would be possible to have a skate boot with any number of lacing sequences or alternations with respect to the shell 12 and the liner 14, as long as a single lace would simultaneously lace-up (*i.e.* co-lace) both the shell 12 and the liner 14. For example a construction wherein the lace would pass twice through the shell and once through the liner, as shown in figure 6, in an alternating fashion, would be within the scope of the present invention. Figure 5 illustrates another embodiment wherein the lace passes twice through the liner and once through the shell.

Moreover, it is not necessary that the lacing means be specifically secured by an eyelet 18 on the shell 12 and by a strap 22 on the liner 14. On either the shell 12 or the liner 14 the lace could be secured by eyelets, straps, hooks, or by any other conventional structure known to those skilled in the art. In this  
5 respect, in the embodiment illustrated in figures 2 and 4, the straps 22 on the liner 14 of figure 1 have been replaced by eyelets 24.

Figure 3 illustrates a similar embodiment with an exploded perspective view. In this example, the liner 14 has three pairs of liner attachment means 24, and the  
10 shell 12 has four pairs of shell attachment means 18.

According to the invention, when the skate is laced and the lace 20 is pulled tight, the liner 14 will become tightened about the foot of the skater, and simultaneously, the shell 12 will become tightened about the liner. This  
15 synchronous tightening will provide a better, more snug fit, between the shell 12, the liner 14 and the skater's foot. In addition, as the shell 12 and the liner 14 are co-laced, the movement of the liner 14 within the shell 12 will be further limited as compared with prior art skate boot constructions.

20 The above description of preferred embodiments should not be interpreted in a limiting manner since other variations, modifications and refinements are possible within the spirit and scope of the present invention. The scope of the invention is defined in the appended claims and their equivalents.



**CLAIMS**

1. A lacing system for a boot, said boot comprising a first outer member and a second inner member, said lacing system comprising a first set of attachment means provided on said first outer member, and a second set of attachment means provided on said second inner member, wherein at least a pair of attachment means of each set is disposed such that a single lacing means provided on said boot is capable to engage alternately the first outer member and the second inner member.
2. A lacing system as defined in claim 1, wherein the attachment means comprises eyelets.
3. A lacing system as defined in claim 1, wherein the attachment means comprises straps.
4. A lacing system as defined in claim 1, wherein the attachment means comprises hooks.
5. A skate boot comprising an outer shell and an inner liner, said shell and liner being provided with an opening generally adapted to substantially correspond at least partially with a portion of the dorsal area of the foot of the wearer, said liner and said shell being provided with attachment means for engagement with a lace, said attachment means being disposed such that at least a pair of said attachment means of said shell is disposed adjacent a pair of said attachment means of said liner to form an alternate lacing arrangement.

6. A skate boot as defined in claim 5, wherein said lacing arrangement is such that a lacing means provided on said boot is capable to alternately engage said liner attachment means and said shell attachment means.


5 7. A skate boot as defined in claim 5, wherein the attachment means comprises eyelets.

8. A skate boot as defined in claim 5, wherein the attachment means comprises straps.


10

9. A skate boot as defined in claim 5, wherein the attachment means comprises hooks.

1/3




**Fig.1**




**Fig.2**


2/3

**Fig.3**


3/3



**Fig. 4**



**Fig. 5**



**Fig. 6**

# INTERNATIONAL SEARCH REPORT

Inter. Appl. No.  
PCT/CA 98/00154

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 6    A43B5/16    A43C1/00    A43B5/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 6    A43B    A43C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	EP 0 784 944 A (SALOMON) 23 July 1997 see the whole document	1-5
X	WO 89 04126 A (TMC) 18 May 1989 see the whole document	1-4
P, A	EP 0 796 571 A (SALOMON) 24 September 1997 see the whole document	1, 5
A	DE 11 91 717 B (F. FESL) 22 April 1965 see the whole document	1
<div style="display: flex; justify-content: space-between;"> <div> <input type="checkbox"/> Further documents are listed in the continuation of box C.         </div> <div> <input checked="" type="checkbox"/> Patent family members are listed in annex.         </div> </div>		
<div style="display: flex;"> <div style="flex: 1;"> <p>* Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search  <div style="text-align: center; font-weight: bold;">27 May 1998</div>		Date of mailing of the international search report  <div style="text-align: center; font-weight: bold;">05/06/1998</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fac (+31-70) 340-3018		Authorized officer  <div style="text-align: center; font-weight: bold;">Declerck, J</div>

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Patent Application No

PCT/CA 98/00154

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0784944 A	23-07-1997	FR 2743730 A CA 2195502 A	25-07-1997 23-07-1997
WO 8904126 A	18-05-1989	AT 396542 B CS 8807282 A DE 3868265 A EP 0340267 A FI 892290 A,B HU 65196 A,B JP 2501807 T SU 1762741 A US 5154011 A	27-09-1993 18-11-1992 12-03-1992 08-11-1989 11-05-1989 02-05-1994 21-06-1990 15-09-1992 13-10-1992
EP 0796571 A	24-09-1997	FR 2745989 A CA 2197397 A	19-09-1997 19-09-1997
DE 1191717 B		NONE	